

# Three-way mixing valves

Submittal information

Date submitted:

## Project Information

Job name :	Location :
Engineer :	Date submitted:
Contractor :	Submitted by:
Manufacturer's representative :	Approved by :

## Product information and application use

N/A



Part name	Part no.	A [inch]	B [inch]	C [inch]	Weight per UOM [lbs/UOM]
3/4" Three-way Mixing Valve, (CV=4.5)	A3040075	4.702	4.383	2.42	1.5
1" Three-way Mixing Valve, (CV=4.5)	A3040100	4.702	4.383	2.42	1.5

Installation	Related applications
N/A	-

Codes	Standards	Listings
-	Class II wiring	-

## Notes

3/4" Cv=4.5  
 Service:  
 Closed-system hot and cold water  
 Maximum 50% glycol

1" Cv=4.5  
 Service:  
 Closed-system hot and cold water  
 Maximum 50% glycol  
 Maximum operating pressure: 300 psi (2,100 kPa)  
 Maximum shutoff pressure: 125 psi (875 kPa)

## Trademark Information

ProPEX® is a registered trademark of Uponor Inc. ProPEX™ is a trademark of Uponor Ltd.

## Contact information

Uponor Inc.  
 5925 148th Street West  
 Apple Valley, MN 55124  
 T 800.321.4739  
 F 952.891.2008

Uponor Ltd.  
 6510 Kennedy Road  
 Mississauga, ON L5T 2X4  
 T 888.594.7726  
 F 800.636.9517