

Copper valved manifold accessories - Ball and balancing valve copper adapter



Project information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Material	Brass
Subcomponent Material	CA 360 Brass
End type 2	Sweat 3/4"
Cold working pressure	246.6 psi
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar)
	180 °F (82 °C) at 100 psi (6.9 bar)
	200 °F (93 °C) at 80 psi (5.5 bar)
Prop 65 label required?	Yes



Product information and application use

The Uponor Ball and Balancing Valves include 3/4" copper adapters and feature in-line isolation valves.

Part name	Part no.	A [mm]	B [mm]	C [mm]	End Type 1	Weight per UOM [kg/UOM]
Ball and Balancing Valve, R20 Thread x 3/4" Copper Adapter	A5902075	101.60	54.17	25.40	ISO 228-G 3/4"	0.376
Ball and Balancing Valve, R25 Thread x 3/4" Copper Adapter	A5902575	104.13	58.93	35.81	ISO 228-G 1"	0.3629

Part name	Part no.	Codes	Standards	Listings
Copper valved manifold accessories - Ball and balancing valve copper adapter	All	-	CSA B125 ASME A112.18.1	-

Installation

Install valve according to local building code. Do not dismantle. If soldering, aim flame away from fitting. For more information, refer to the AquaPEX® Professional Plumbing Installation Guide or Radiant Floor Installation Handbook.

Related applications

- PEX-a Plumbing Systems
- Radiant Heating and Cooling Systems
- Permafrost Protection Systems
- Turf Conditioning Systems

Footnotes

Contact information

-	Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008	Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517
---	---	---