

ProPEX lead-free (LF) brass commercial ball valve stem extension kits



Project Information

| | |
|---------------------------------|-----------------|
| Job name : | Location : |
| Engineer : | Date submitted: |
| Contractor : | Submitted by: |
| Manufacturer's representative : | Approved by : |

Technical data

Material Galvanized steel

Product information and application use

To help meet the stringent demands of commercial plumbing and hydronic distribution projects, Uponor is offering new ProPEX® ASTM F1960 lead-free (LF) brass ball valves in sizes from ½" to 2". The full-port ball valves feature a stainless-steel ball and stem for greater durability, longevity, and system performance.



| Part name | Part no. | A [inch] | B [inch] | C [inch] | D [inch] | Weight per UOM [lbs/UOM] |
|---|----------|----------|----------|----------|----------|--------------------------|
| 2 3/8" Stem Extension Kit for 1/2" and 3/4" LFCSS Ball Valves | F6630001 | 3.3 | 1.02 | 1.02 | 2.82 | 0.39 |
| 2 5/8" Stem Extension Kit for 1" and 1 1/4" LFCSS Ball Valves | F6630002 | 3.4 | 1.293 | 1.293 | 2.8 | 0.66 |
| 2 5/8" Stem Extension Kit for 1 1/2" and 2" LFCSS Ball Valves | F6630003 | 3.57 | 1.369 | 1.369 | 2.88 | 0.77 |

Installation

Install valve and stem extension kit according to local building code. Do not dismantle. Refer to the Uponor Piping Pocket Guide or the Uponor Plumbing Design Assistance Manual (PDAM) for additional information.

Related applications

- Hot water distribution
- Hydronic heating and cooling systems
- Hydronic Piping Systems
- Hydronic Radiant Heating and Cooling Systems
- PEX-a Plumbing Systems
- Plumbing Systems
- Pre-Insulated Pipe Systems
- Radiant Heating and Cooling Systems

Codes

Standards

Listings

-

Footnotes

Contact information

| | | |
|---|---|---|
| - | Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008 | Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.636.9517 |
|---|---|---|