

# ProPEX lead-free (LF) brass fire sprinkler accessories

## Project information

Job name :	Location :
Engineer :	Date submitted:
Contractor :	Submitted by:
Manufacturer's representative :	Approved by :

## Technical data

End type 1	ProPEX 1/2"
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)
Prop 65 label required?	Yes



Part name	Part no.	A [inch]	B [inch]	C [inch]	Weight per UOM [lbs/UOM]	Equivalent length branch [ft]	Material group
Fire Sprinkler Adapter Mounting Bracket, 3/4" and 1	A7750700	3.171	2.484	1.839	0.17	-	-
Fire Sprinkler Adapter Push-on Nut, 25/pkg.	F7000005	2.125	0.233	2.125	0.01	0	-
Screws, #10 x 1 1/2", Pan Head, Full Thread, 100/pkg.	F7001500	-	-	-	-	-	-

## Installation

-

## Related applications

AquaSAFE™ Fire Safety Systems

## Codes

-

## Standards

UL 1821

## Listings

-

## Footnotes

-

## Contact information

Uponor Inc.  
5925 148th Street West  
Apple Valley, MN 55124  
T 800.321.4739  
F 952.891.2008

Uponor Ltd.  
6510 Kennedy Road  
Mississauga, ON L5T 2X4  
T 888.594.7726  
F 800.636.9517