# PEX-a pipe supports

## Project information

| | |
|---|---|
| Job name: | Location: |
| Engineer: | Date submitted: |
| Contractor: | Submitted by: |
| Manufacturer's representative: | Approved by: |

## Product information and application use

PEX-a Pipe Support is a non-combustible, self-gripping, galvanized-steel channel for crosslinked polyethylene (PEX-a) pipe. It provides continuous, uninterrupted support of PEX-a pipe, allowing hanger placement similar to that of metallic pipe. Use PEX-a Pipe Support in conjunction with un-insulated Uponor AquaPEX® or Wirsbo hePEX™ PEX-a pipe in ASTM E84 plenum applications. The PEX-a pipe with pipe support can be insulated with typical CTS (copper tube size) pipe insulation. PEX-a Pipe Support is offered in 9-foot lengths and comes with nylon-coated, stainless-steel strapping.



| | Part name | Part no. | A [mm] | B [mm] | C [mm] | Material group | Subcomponent Material | Prop 65 label required? | Weight per UOM [kg/UOM] |
|---|---|---|---|---|---|---|---|---|---|
| | 1/2" PEX-a Pipe Support, 9-ft. length | F7040500 | 2743.20 | 17.20 | 10.31 | Metal | Commercial-grade (Type B) galvanized steel | - | 0.4989522004 |
| | 3/4" PEX-a Pipe Support, 9-ft. length | F7040750 | 2743.20 | 23.39 | 14.02 | Metal | Commercial-grade (Type B) galvanized steel | No | 0.6803893642 |
| | 1" PEX-a Pipe Support, 9-ft. length | F7041000 | 2743.20 | 29.54 | 17.73 | Metal | Commercial-grade (Type B) galvanized steel | - | 0.866362457 |
| | 1 1/4" PEX-a Pipe Support, 9-ft. length | F7041250 | 2743.20 | 35.46 | 21.26 | Metal | Commercial-grade (Type B) galvanized steel | - | 0.9525451098 |
| | 1 1/2" PEX-a Pipe Support, 9-ft. length | F7041500 | 2743.20 | 41.22 | 24.71 | Metal | Commercial-grade (Type B) galvanized steel | - | 1.133982274 |
| | 2" PEX-a Pipe Support, 9-ft. length | F7042000 | 2743.20 | 53.21 | 31.90 | Metal | Commercial-grade (Type B) galvanized steel | - | 1.632934474 |
| ✔ | 2 1/2" PEX-a Pipe Support, 9-ft. length | F7042500 | 2743.20 | 65.07 | 39.04 | Metal | Commercial-grade (Type B) galvanized steel | - | 2.086527383 |
| | PEX-a Pipe Support Strapping for 1/2", 3/4" and 1" PEX | Q7410510 | - | - | - | Plastic | - | - | 0.0018 |
| | 3" PEX-a Pipe Support, 9-ft. length | F7043000 | 2743.20 | 76.81 | 45.97 | Metal | Commercial-grade (Type B) galvanized steel | - | 2.812276039 |
| | PEX-a Pipe Support Strapping for 1 1/4", 1 1/2" and 2" PEX | Q7411220 | - | - | - | Plastic | - | - | 0.0036 |
| | PEX-a Pipe Support Strapping for 2 1/2", 3", 3 1/2" PEX | Q7412540 | - | - | - | Plastic | - | - | 0.0059 |

| Part name | Part no. | Codes | Standards | Listings |
|---|---|---|---|---|
| PEX-a pipe supports | All | IMC\|UMC | ASTM E84 | QAI P321 (up to 3") |

## Installation

Install PEX-a Pipe Support vertically or horizontally for plenum and non-plenum applications. Refer to the Uponor PEX-a Pipe Support Instruction Sheet for installation guidelines.

## Related applications

PEX-a Plumbing Systems

Radiant Heating and Cooling Systems

AquaSAFE™ Fire Safety Systems

© 2024 Uponor North America. All Rights Reserved

| Footnotes | Contact information | |
|---|---|---|
| | Uponor Inc.<br>5925 148th Street West<br>Apple Valley, MN 55124<br>T 800.321.4739<br>F 952.891.2008 | Uponor Ltd.<br>6510 Kennedy Road<br>Mississauga, ON L5T 2X4<br>T 888.594.7726<br>F 800.638.9517 |
| - | | |

© 2024 Uponor North America. All Rights Reserved