υροποι

ProPEX to MIP lead-free (LF) brass ball valves


Project information	
Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data	
Material	LF Brass
End type 1	ProPEX 1/2"
End type 2	MNPT 1/2"
Cold working pressure	249.5 psi
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar)
	180 °F (82 °C) at 100 psi (6.9 bar)
	200 °F (93 °C) at 80 psi (5.5 bar)
	210 °F (99 °C) at 149 psi (10.3 bar)
Prop 65 label required?	Yes

Product information and application use

 $\label{eq:ProPEX® Lead-free Ball Valve features a shut-off valve between $$\frac{1}{2}$" Uponor AquaPEX® tubing and $$\frac{1}{2}$" male iron pipe (MIP). 1 These valves are not compatible with applications using glycol.$

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.



Part name	Part no.	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	F [mm]	G [mm]	H [mm]	l [mm]	J [mm]
ProPEX LF Brass Ball Valve, 1/2" PEX x 1/2" MIP	LF4795050	18	30.71	29.38	22.35	15.37	29.33	25.40	62.45	42.08	51.44

Part name	Part no.	K [mm]	Weight per UOM [kg/UOM]
ProPEX LF Brass Ball Valve, 1/2" PEX x 1/2" MIP	LF4795050	12.70	0.1542

Part name	Part no.	Codes	Standards	Listings
ProPEX to MIP lead-free (LF) brass ball valves	LF4795050	UPC IRC IPC NPC of Canada	NSF-372 ASME A112.18.1 ASTM F877 ASTM F1960 CSA B125 CSA B137.5 NSF-61 NSF-14	cNSFus-pw-G U.P.Code

Installation

Install valve according to local building code. Do not dismantle. If soldering, aim flame away from fitting. For more information, refer to the Uponor Professional Plumbing Installation Guide.

PEX-a Plumbing Systems

Related applications

- Contact information - 1000 Contact information - 1000