EP branch multi-port tees

Project information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:


Technical data

Material	Engineered Polymer
End type 2	ProPEX 1/2"
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)

Product information and application use

Engineered polymer (EP) branch multi-port tees are used in hot and cold domestic potable water distribution systems. The multi-port tees are available with ¾" or 1" ProPEX® inlets and ½" ProPEX outlets. 1

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.



	Part name	Part no.	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	F [mm]	G [mm]	H [mm]	End Type 1	Weight per UOM [kg/UOM]
✔	3/4" EP Branch Multi-port Tee, 3 (1/2") outlets	Q2237550	112.52	24.26	15.88	31.75	12.19	18.26	41.63	30.99	ProPEX 3/4"	0.045
	3/4" EP Branch Multi-port Tee, 4 (1/2") outlets	Q2247550	145.54	24.26	15.88	31.75	12.19	18.26	41.63	30.99	ProPEX 3/4"	0.059
	1" EP Branch Multi-port Tee, 4 (1/2") outlets	Q2241050	169.95	30.25	19.69	31.75	15.24	18.26	47.73	37.59	ProPEX 1"	0.077
	3/4" EP Branch Multi-port Tee, 6 (1/2") outlets	Q2267550	226.12	24.26	15.88	31.75	11.62	18.26	41.25	29.97	ProPEX 3/4"	0.082
	1" EP Branch Multi-port Tee, 6 (1/2") outlets	Q2261050	234.98	30.25	15.88	31.75	14.48	18.26	51.04	36.60	ProPEX 1"	0.113

Part name	Part no.	Codes	Standards	Listings
EP branch multi-port tees	All	UPC|IBC|IRC|IPC|NPC of Canada|UMC|NSPC|IMC	ASTM E814/ULC S115|ASTM F877|ASTM F1960|CSA B137.5|ULC S102.2|ASTM E119/UL 263|NSF-61|ULC S101|NSF-14	IAPMO-ES|HUD MR 1269|ICC-ES-PMG|cNSFus-pw|UL|U.P.Code|cQAIus P321

Installation

For a mounting bracket, use any product designed to mount 1" copper pipe for the ¾" multi-port tee or 1¼" copper pipe for the 1" multi-port tee. For more information, refer to the Uponor Piping Systems Installation Guide.

Related applications

PEX-a Plumbing Systems

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517

© 2024 Uponor North America. All Rights Reserved