

Copper valved manifolds with ProPEX ball and balancing valves



Project information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Material	Copper
Manifold size	2 inch
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar) 210 °F (99 °C) at 149 psi (10.3 bar)
Max. fluid flow rate	45 gpm
Prop 65 label required?	Yes



Product information and application use

Uponor offers 2" Copper Valved Manifold with ProPEX® Ball and Balancing Valves for radiant heating projects.1 The manifold has a 2" Copper Sweat Fitting Adapter supply connection and ¾" nominal branches. This 12-outlet manifold is preassembled with ⅝" or ¾" ProPEX balancing valve connections.

Part name	Part no.	A [mm]	B [mm]	C [mm]	Cv Branch	End Type 1	Weight per UOM [kg/UOM]
2" x 4' Copper Valved Manifold with ⅝" ProPEX Ball and Balancing Valves, 12 outlets	Q2821263	1219.20	197.87	66.87	6.6	ProPEX ⅝"	6.9173
2" x 4' Copper Valved Manifold with ¾" ProPEX Ball and Balancing Valves, 12 outlets	Q2821275	1219.20	199.92	66.87	6.7	ProPEX ¾"	6.9173

Part name	Part no.	Codes	Standards	Listings
Copper valved manifolds with ProPEX ball and balancing valves	All	-	CSA B137.5 ASTM F877	cNSFus-rfh

Installation

Install using any product designed to mount 2" copper pipe as a mounting bracket. Refer to the Uponor Radiant Floor Heating Installation Handbook for additional information.

Related applications

- Radiant Heating and Cooling Systems
- Permafrost Protection Systems
- Turf Conditioning Systems

Notes

Ball Valve Cv " outlet: 6.60
Ball Valve Cv ¾" outlet: 6.70

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517