

ProPEX baseboard elbows

| Project information | |
|--------------------------------|-----------------|
| Job name: | Location: |
| Engineer: | Date submitted: |
| Contractor: | Submitted by: |
| Manufacturer's representative: | Approved by: |

Technical data

Material Brass
End type 2 Sweat 3/4"


Temp/pressure ratings 73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar)

180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)

Prop 65 label required? Yes

Product information and application use

The Uponor ProPEX® Baseboard Tee Copper Adapter can be used in any heating system applying the use of fin-tube baseboard or unit-type heaters.1 One end of the tee adapter features a ProPEX fitting for an easy transition from copper pipe to Wirsbo hePEXTM tubing or Uponor AquaPEX® tubing.



| Part name | Part no. | A [mm] | B [mm] | C [mm] | D [mm] | E [mm] | F [mm] | G [mm] | H [mm] | End Type 1 | Weight per UOM [kg/UOM] |
|-------------------------------------------------------------------|-------------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|------------------|-------------------------------|
| ProPEX Baseboard Elbow, 1/2" PEX x 3/4" Copper Adapter | Q4385075 | 45.62 | 7.80 | 37.82 | 15.52 | 18 | 45.97 | 25.07 | 19.05 | ProPEX 1/2" | 0.077 |
| ProPEX Baseboard Elbow, 5/8" PEX x 3/4" Copper Adapter | Q4386375 | 47.27 | 9.45 | 37.82 | 15.60 | 22 | 50.13 | 26.42 | 19.05 | ProPEX 5/8" | 0.078 |
| ProPEX Baseboard Elbow, 3/4" PEX x 3/4" Copper Adapter | Q4387575 | 48.87 | 11.05 | 37.82 | 15.62 | 24 | 52.16 | 30.48 | 19.05 | ProPEX 3/4" | 0.163 |
| ProPEX Baseboard Elbow, 1/2" PEX x 3/4" Copper Fitting Adapter | Q4375075 | 45.62 | 7.80 | 37.82 | 15.52 | 18 | 45.97 | 25.07 | 20.57 | ProPEX 1/2" | 0.172 |
| ProPEX Baseboard Elbow, 5/8" PEX x 3/4" Copper Fitting Adapter | Q4376375 | 47.27 | 9.45 | 37.82 | 15.60 | 22 | 51.56 | 26.42 | 20.57 | ProPEX 5/8" | 0.172 |
| ProPEX Baseboard Elbow, 3/4" PEX x 3/4" Copper Fitting Adapter | Q4377575 | 48.87 | 11.05 | 37.82 | 15.62 | 24 | 54.10 | 30.48 | 20.57 | ProPEX 3/4" | 0.092 |

| Part name | Part no. | Codes | Standards | Listings |
|-------------------------|----------|-------|--------------------------------------------|--------------------------------|
| ProPEX baseboard elbows | All | IMC | ASTM F1960 CSA B137.5 NSF- 14 ASTM F877 | IAPMO-ES ICC-ES-PMG cNSFus-rfh |

Installation Related applications

Use the appropriate ProPEX Ring for tubing (sold separately). Do not solder within 18 inches of the ProPEX connection. Refer to the Uponor Radiant Floor Heating Installation Handbook for additional information.

Radiant Heating and Cooling Systems

Permafrost Protection Systems

Turf Conditioning Systems

AquaSAFE™ Fire Safety Systems

| Footnotes | Contact i | Contact information | | |
|-----------|------------------------|-------------------------|--|--|
| | Uponor Inc. | Uponor Ltd. | | |
| | 5925 148th Street West | 6510 Kennedy Road | | |
| | Apple Valley, MN 55124 | Mississauga, ON L5T 2X4 | | |
| | T 800.321.4739 | T 888.594.7726 | | |
| | F 952.891.2008 | F 800.638.9517 | | |