

Transformers

| Project information | |
|--------------------------------|-----------------|
| Job name: | Location: |
| Engineer: | Date submitted: |
| Contractor: | Submitted by: |
| Manufacturer's representative: | Approved by: |

Technical data

Prop 65 label required? Yes

Product information and application use

The 50 VA Transformer (24VAC) features a foot or hub mount for a 2" x 2" or 4" x 4" electrical box



| Part name | Part no. | A [m m] | B [m m] | C [m m] | Current draw max. [A] | Operating voltage [V] | Operating voltage AC [VAC] | Voltage secondary AC (50VA) [VAC] | Output rating at 24VAC [A] | Weight per UOM [kg/UOM] |
|-------------------|-------------|---------------|---------------|---------------|--------------------------------|-----------------------|----------------------------|---|--|-------------------------------|
| 50 VA Transformer | A3050050 | 112.32 | 63.50 | 76.33 | 0.55 | 24 | 120 | 24 | 2.1 | 1.162 |

| Installation | Related applications |
|---|-------------------------------------|
| When mounting transformer in a knockout, install in a metal box only. Refer to the Uponor Radiant | Radiant Heating and Cooling Systems |

Notes

Primary: White - Black, 120 V, 60 Hz, 0.55 A

| Footnotes | Contact information | | | |
|-----------|------------------------|-------------------------|--|--|
| | Uponor Inc. | Uponor Ltd. | | |
| | 5925 148th Street West | 6510 Kennedy Road | | |
| | Apple Valley, MN 55124 | Mississauga, ON L5T 2X4 | | |
| | T 800.321.4739 | T 888.594.7726 | | |
| | F 952.891.2008 | F 800.638.9517 | | |