Product data sheet



GF Uponor Uni-C end plug O-ring MT 1"

1002274

- Made of tin-plated DR brass (lead-free)
- sealing element with elastomer O-ring
- designed for closing unused Uni-C connections
- resistant to drinking water and aging
- suitable for potable water installations



Application information GF Uponor Uni-C end plug O-ring MT

Specification

- Modular brass manifold system with male threaded connections
- Components made of tin-plated or plated brass; brackets in galvanised steel
- Compatible with ½" Uni-C compression adapters for MLC and Uni Pipe PLUS pipes
- Thread standards according to EN ISO 228-1 / DIN
- System includes manifolds, valves, end caps, plugs, brackets, couplings, and adapters

Application

- Distribution and connection of tap water
- Manifold-based installations with male threaded connections
- Adaptation between Uponor pipe systems (Uni Pipe PLUS, MLC) and Uponor ½" threaded components
- Use in residential and light commercial installations
- Flexible system extension via manifolds, adapters, and accessories

GF Uponor Uni-C end plug O-ring MT 1"

1002274



Product code

Item no EAN	6414905514908
Item no GF	35001002274
Item no GTIN	06414905514908

Dimensions

Item Unit Height	40
Item Unit Length	20
Item Unit Weight	0,1
Item Unit Width	20
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905564873
Packaging GTIN PL3	06414905564880
Packaging Height PL1	15
Packaging Height PL3	200
Packaging Length PL1	200
Packaging Length PL3	400
Packaging Quantity PL1	10
Packaging Quantity PL3	20
Packaging Type PL1	Plastic_Bag
Packaging Type PL3	Box
Packaging Volume PL1	0,0003
Packaging Volume PL3	0,0236
Packaging Weight PL1	1,01
Packaging Weight PL3	2,02
Packaging Width PL1	100

Packaging Width PL3	295

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+