Product data sheet



GF Uponor S-Press jaw UPP1 16

1007084

- pressing jaws for Uponor MLC press fittings



Application information GF Uponor S-Press jaw UPP1

Specification

- with fixed press sleeve
- stop ring
- test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:
Male and female threads acc.to EN 10226-1.

GF Uponor S-Press jaw UPP1 16

1007084



Product code

Item no EAN	4021598100138
Item no GF	35001007084
Item no GTIN	04021598100138
Item no LVI	1725923
Item no NOBB	46853656
Item no NRF	5071851
Item no RSK	1876991
Item no VVS	045498116

Dimensions

Item Unit Height	40
Item Unit Length	15
Item Unit Weight	1,91
Item Unit Width	105
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905433483
Packaging GTIN PL4	06414900310123
Packaging Height PL1	55
Packaging Height PL4	500
Packaging Length PL1	180
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	216
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet

Packaging Volume PL1	0,001188
Packaging Volume PL4	0,48
Packaging Weight PL1	1,98
Packaging Weight PL4	437,56
Packaging Width PL1	120
Packaging Width PL4	800

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+