Product data sheet



GF Uponor S-Press jaw UPP1 20

1007086

- pressing jaws for Uponor MLC press fittings



Application information GF Uponor S-Press jaw UPP1

Specification

- with fixed press sleeve
- stop ring
- test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:
Male and female threads acc.to EN 10226-1.

GF Uponor S-Press jaw UPP1 20

1007086



Product code

Item no EAN	4021598100152
Item no GF	35001007086
Item no GTIN	04021598100152
Item no LVI	1725924
Item no NOBB	46853660
Item no NRF	5071853
Item no RSK	1876992
Item no VVS	045498120

Dimensions

Item Unit Height	30
Item Unit Length	150
Item Unit Weight	1,9
Item Unit Width	120
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905433490
Packaging Height PL1	60
Packaging Length PL1	185
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,001332
Packaging Weight PL1	2
Packaging Width PL1	120

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+