Product data sheet



GF Uponor S-Press jaw UPP1 32

1007088

- pressing jaws for Uponor MLC press fittings



Application information GF Uponor S-Press jaw UPP1

Specification

- with fixed press sleeve
- stop ring
- test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:
Male and female threads acc.to EN 10226-1.

GF Uponor S-Press jaw UPP1 32

1007088



Product code

Item no EAN	4021598100176
Item no GF	35001007088
Item no GTIN	04021598100176
Item no LVI	1725926
Item no NOBB	46853686
Item no NRF	5071855
Item no RSK	1876994
Item no VVS	045498132

Dimensions

Item Unit Height	35
Item Unit Length	152
Item Unit Weight	2,0
Item Unit Width	105
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905433513
Packaging Height PL1	55
Packaging Length PL1	180
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,001188
Packaging Weight PL1	2,05
Packaging Width PL1	120

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+