Product data sheet



GF Uponor S-Press jaw Mini KSP0 16

1007091

- Uponor pressing jaws MLC Mini KSP0



Application information GF Uponor S-Press jaw Mini KSP0

Specification

- with fixed press sleeve
- stop ring
- test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:
Male and female threads acc.to EN 10226-1.

GF Uponor S-Press jaw Mini KSP0 16

1007091



Product code

Item no EAN	4021598100206
Item no GF	35001007091
Item no GTIN	04021598100206
Item no LVI	1725943
Item no NOBB	47367615
Item no NRF	5071288
Item no RSK	1877185
Item no VVS	045498416

Dimensions

Item Unit Height	17
Item Unit Length	125
Item Unit Weight	1,02
Item Unit Width	95
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905433537
Packaging GTIN PL3	06414905444793
Packaging Height PL1	19
Packaging Height PL3	120
Packaging Length PL1	127
Packaging Length PL3	200
Packaging Quantity PL1	1
Packaging Quantity PL3	5
Packaging Type PL1	Plastic_Bag
Packaging Type PL3	Box

Packaging Volume PL1	0,000234061
Packaging Volume PL3	0,0048
Packaging Weight PL1	1,022
Packaging Weight PL3	5,2
Packaging Width PL1	97
Packaging Width PL3	200

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+