
Product data sheet



GF Uponor S-Press jaw Mini KSP0 20

1007093

- Uponor pressing jaws MLC Mini KSP0



Application information GF Uponor S-Press jaw Mini KSP0

Specification

- with fixed press sleeve
- stop ring
- test safety

Application


- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:
Male and female threads acc.to EN 10226-1.

GF Uponor S-Press jaw Mini KSP0 20

1007093



Product code

Item no EAN	4021598100220
Item no GF	35001007093
Item no GTIN	04021598100220
Item no LVI	1725944
Item no NOBB	47367626
Item no NRF	5071289
Item no RSK	1877186
Item no VVS	045498420

Dimensions

Item Unit Height	17
Item Unit Length	155
Item Unit Weight	1
Item Unit Width	95
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905433544
Packaging GTIN PL3	06414905444809
Packaging Height PL1	19
Packaging Height PL3	120
Packaging Length PL1	157
Packaging Length PL3	170
Packaging Quantity PL1	1
Packaging Quantity PL3	5
Packaging Type PL1	Plastic_Bag
Packaging Type PL3	Box

Packaging Volume PL1	0,000289351
Packaging Volume PL3	0,004284
Packaging Weight PL1	1,01
Packaging Weight PL3	5,15
Packaging Width PL1	97
Packaging Width PL3	210

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+