

Uponor Vario PLUS manifold kit K1

1009209

- Including brackets, flat sealing screw connection pieces with swivel nut, thermometer and end pieces with air vent, filling and draining tap and a by-pass



Application information Uponor Vario PLUS manifold kit

Specification

- Modular fibre glass reinforced polyamide manifold with 1,3,4,6 loops for connection with basic kit
- connection right or left with flat sealing or connection from below with optional elbowset
- supply with lockshield (LS) valve for balancing with adjusting ring or supply with Flowmeter (FM) for balancing
- shut-off and flow view
- adjusting ring for balancing without tools
- prepared places for room name labels
- return with valves and caps, prepared for actuators
- loop connection G3/4" eurocone
- loop pitch 50 mm
- header pitch 225 mm

Actuator:

- NC (normally closed) = closes without power

Application

- for underfloor heating and cooling
- can be combined with actuators MT 30x1,5

Certification

- CE

Uponor Vario PLUS manifold kit K1

1009209



Product code

Item no EAN	4016203841100
Item no GF	35001009209
Item no GTIN	04016203841100
Item no LVI	2026801
Item no NOBB	41947882
Item no NRF	8362652
Item no RSK	2418963
Item no VVS	466247124

Dimensions

Item Unit Height	320
Item Unit Length	15
Item Unit Weight	0,73
Item Unit Width	50
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905256006
Packaging GTIN PL4	06414905525454
Packaging Height PL1	97
Packaging Height PL4	950
Packaging Length PL1	325
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	248
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,002679625
Packaging Volume PL4	0,912

Packaging Weight PL1	0,78
Packaging Weight PL4	218,44
Packaging Width PL1	85
Packaging Width PL4	800

Documents

Page with all documents 

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com