

Uponor Vario PLUS manifold kit K1

1009209

- Including brackets, flat sealing screw connection pieces with swivel nut, thermometer and end pieces with air vent, filling and draining tap and a by-pass



Application information Uponor Vario PLUS manifold kit

Specification

- Modular fibre glass reinforced polyamide manifold with 1,3,4,6 loops for connection with basic kit
- connection right or left with flat sealing or connection from below with optional elbowset
- supply with lockshield (LS) valve for balancing with adjusting ring or supply with Flowmeter (FM) for balancing
- shut-off and flow view
- adjusting ring for balancing without tools
- prepared places for room name labels
- return with valves and caps, prepared for actuators
- loop connection G3/4" eurocone
- loop pitch 50 mm
- header pitch 225 mm

Actuator:

- NC (normally closed) = closes without power

Application

- for underfloor heating and cooling
- combineable with actuators MT 30x1,5

Certification

- CE

Uponor Vario PLUS manifold kit K1

1009209



Technical data

Item (unit of measurement)	pce
Item no VVS	466247124
Item no LVI	2026801
Item no NRF	8362652
Packaging Quantity PL1	1
Packaging Quantity PL4	248

Documents

Page with all documents 

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E info@uponor.com
F +358 (0)20 129 2841

www.uponor.com