

Uponor Vario PLUS flowmeter 4 l/min

1009217

- With shut-off function



Application information Uponor Vario PLUS flowmeter

Specification

- Modular fibre glass reinforced polyamide manifold with 1,3,4,6 loops for connection with basic kit
- connection right or left with flat sealing or connection from below with optional elbowset
- supply with lockshield (LS) valve for balancing with adjusting ring or supply with Flowmeter (FM) for balancing
- shut-off and flow view
- adjusting ring for balancing without tools
- prepared places for room name labels
- return with valves and caps, prepared for actuators
- loop connection G3/4" eurocone
- loop pitch 50 mm
- header pitch 225 mm

Actuator:

- NC (normally closed) = closes without power

Application

- for underfloor heating and cooling
- combineable with actuators MT 30x1,5

Certification

- CE

Uponor Vario PLUS flowmeter 4 l/min

1009217



Technical data

Item (unit of measurement)	pce
Item no VVS	087604107
Item no LVI	2025708
Item no NRF	8362672
Length (l)	146 mm
Length (l1)	74 mm
Packaging Quantity PL1	1
Packaging Quantity PL3	20

Documents

[Page with all documents](#) 

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E info@uponor.com
F +358 (0)20 129 2841

www.uponor.com