

Uponor Vario PLUS flowmeter 4 l/min

1009217

- With shut-off function



Application information Uponor Vario PLUS flowmeter

Specification

- Modular fibre glass reinforced polyamide manifold with 1,3,4,6 loops for connection with basic kit
- connection right or left with flat sealing or connection from below with optional elbowset
- supply with lockshield (LS) valve for balancing with adjusting ring or supply with Flowmeter (FM) for balancing
- shut-off and flow view
- adjusting ring for balancing without tools
- prepared places for room name labels
- return with valves and caps, prepared for actuators
- loop connection G3/4" eurocone
- loop pitch 50 mm
- header pitch 225 mm

Actuator:

- NC (normally closed) = closes without power

Application

- for underfloor heating and cooling
- can be combined with actuators MT 30x1,5

Certification

- CE

Uponor Vario PLUS flowmeter 4 l/min

1009217



Product code

Item no EAN	4016203841872
Item no GF	35001009217
Item no GTIN	04016203841872
Item no LVI	2025708
Item no NOBB	41948041
Item no NRF	8362672
Item no RSK	2418982
Item no VVS	087604107

Dimensions

Item Unit Height	150
Item Unit Length	10
Item Unit Weight	0,044
Item Unit Width	20
Item_UOM	pce

Measurements

LENGTH_L	146
Length (l1)	74
Outer Diameter_do	38

Packaging

Packaging GTIN PL1	06414905256068
Packaging GTIN PL3	06414905256075
Packaging Height PL1	145
Packaging Height PL3	100
Packaging Length PL1	38
Packaging Length PL3	390
Packaging Quantity PL1	1
Packaging Quantity PL3	20

Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Volume PL1	0,00020938
Packaging Volume PL3	0,007605
Packaging Weight PL1	0,094
Packaging Weight PL3	1,93
Packaging Width PL1	38
Packaging Width PL3	195

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com