


## Uponor MLC white S 75x7,5 5m

1013453

- bar
- High dimensional stability, low expansion rates
- Increased flexibility
- 100% oxygen barrier



### Application information Uponor MLC white S

#### Specification

- Oxygen diffusion resistant multi-layer composite pipe (PE-RT - adhesive - longitudinally welded aluminium - adhesive - PE-RT)
- Fire classification E according to EN 13501-1.
- With pipe end caps as hygienic seal according to EN 806.

#### Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

#### Certification

- Approvals by local OM.
- E.g.
- DVGW
  - AENOR

## Uponor MLC white S 75x7,5 5m

1013453



### Product code

Item no EAN	4021598010277
Item no GF	35001013453
Item no GTIN	04021598010277
Item no LVI	1720110
Item no NOBB	41940012
Item no NRF	5071339
Item no RSK	1873794
Item no VVS	087306175

### Dimensions

Item Unit Height	75
Item Unit Length	1000
Item Unit Weight	1,812
Item Unit Width	75
Item_UOM	m

### Measurements

Outer Diameter_do	75
Wall thickness_s	7,5

### Packaging

Packaging GTIN PL1	06414900623728
Packaging GTIN PL2	06414905423484
Packaging GTIN PL4	06414905257058
Packaging Height PL1	75
Packaging Height PL2	110
Packaging Height PL4	725
Packaging Length PL1	5000
Packaging Length PL2	5070
Packaging Length PL4	5080

Packaging Quantity PL1	5
Packaging Quantity PL2	5
Packaging Quantity PL4	255
Packaging Type PL1	Bar
Packaging Type PL2	Cover_Pipe
Packaging Type PL4	Wooden_Cage
Packaging Volume PL1	0,028125
Packaging Volume PL2	0,061347
Packaging Volume PL4	4,23545
Packaging Weight PL1	9,06
Packaging Weight PL2	14,34
Packaging Weight PL4	790
Packaging Width PL1	75
Packaging Width PL2	110
Packaging Width PL4	1150

## Documents

Page with all documents



### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211

E  
communications@georgfischer.  
com