Product data sheet



GF Uponor MLC pipe cutting tool blade 50-110

1014173

- for MLC pipes



Application information GF Uponor MLC pipe cutting tool blade

Specification

- Oxygen diffusion resistant multi-layer composite pipe(PE-RT - adhesive - longitudinally welded aluminium - adhesive - PE-RT)
- Fire classification E according to EN 13501-1.
- With pipe end caps as hygienic seal according EN 806.

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

GF Uponor MLC pipe cutting tool blade 50-110

1014173



Product code

Item no EAN	4021598007963
Item no GF	35001014173
Item no GTIN	04021598007963
Item no LVI	1725979
Item no NOBB	41942104
Item no NRF	5071817
Item no RSK	1873350
Item no VVS	045498376

Dimensions

Item Unit Height	11
Item Unit Length	45
Item Unit Weight	0,014
Item Unit Width	45
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905435357
Packaging GTIN PL3	06414905445356
Packaging Height PL1	15
Packaging Height PL3	100
Packaging Length PL1	45
Packaging Length PL3	100
Packaging Quantity PL1	1
Packaging Quantity PL3	20
Packaging Type PL1	Plastic_Bag
Packaging Type PL3	Box

Packaging Volume PL1	0,000030375
Packaging Volume PL3	0,00075
Packaging Weight PL1	0,024
Packaging Weight PL3	0,58
Packaging Width PL1	45
Packaging Width PL3	75

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+