Product data sheet



GF Uponor S-Press jaw UPP1 40

1015768

- pressing jaws for Uponor MLC press fittings





Application information GF Uponor S-Press jaw UPP1

Specification

- with fixed press sleeve
- stop ring
- test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:
Male and female threads acc.to EN 10226-1.

GF Uponor S-Press jaw UPP1 40

1015768





Product code

Item no EAN	4021598302440
Item no GF	35001015768
Item no GTIN	04021598302440
Item no LVI	1725928
Item no NOBB	41942017
Item no NRF	5071808
Item no RSK	1873782
Item no VVS	045498140

Dimensions

Item Unit Height	35
Item Unit Length	170
Item Unit Weight	2,89
Item Unit Width	110
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905436972
Packaging GTIN PL4	06414900310154
Packaging Height PL1	60
Packaging Height PL4	500
Packaging Length PL1	210
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	108
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet

Packaging Volume PL1	0,002205
Packaging Volume PL4	0,48
Packaging Weight PL1	2,99
Packaging Weight PL4	347,92
Packaging Width PL1	175
Packaging Width PL4	800

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+