Product data sheet



GF Uponor S-Press manual tool insert 14

1015776

- For inserting into the manual pressing tool



Application information GF Uponor S-Press manual tool insert

Specification

- with fixed press sleeve
- stop ring
- test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:
Male and female threads acc.to EN 10226-1.

GF Uponor S-Press manual tool insert 14

1015776



Product code

Item no EAN	4021598000094
Item no GF	35001015776
Item no GTIN	04021598000094

Dimensions

Item Unit Height	17
Item Unit Length	30
Item Unit Weight	0,079
Item Unit Width	30
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905436989
Packaging GTIN PL4	06414905490509
Packaging Height PL1	18
Packaging Height PL4	140
Packaging Length PL1	48
Packaging Length PL4	320
Packaging Material (number) PL1	4
Packaging Material PL1	Low density polyethylene
Packaging Material (short) PL1	LDPE
Packaging Quantity PL1	1
Packaging Quantity PL4	400
Packaging Type PL1	Plastic_Bag
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00002592
Packaging Volume PL4	0,010304

Packaging Weight PL1	0,08
Packaging Weight PL4	56,6
Packaging Width PL1	30
Packaging Width PL4	230

Technical data

Recycling Text Block PL1	Low density polyethylene

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+