Product data sheet



GF Uponor S-Press jaw UPP1 50

1015792

- pressing jaws for Uponor MLC press fittings



Application information GF Uponor S-Press jaw UPP1

Specification

- with fixed press sleeve
- stop ring
- test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:
Male and female threads acc.to EN 10226-1.

GF Uponor S-Press jaw UPP1 50

1015792



Product code

Item no EAN	4021598302464
Item no GF	35001015792
Item no GTIN	04021598302464
Item no LVI	1725929
Item no NOBB	41942021
Item no NRF	5071809
Item no RSK	1873783
Item no VVS	045498151

Dimensions

Item Unit Height	32
Item Unit Length	175
Item Unit Weight	2,6
Item Unit Width	118
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905437016
Packaging GTIN PL4	06414900310161
Packaging Height PL1	60
Packaging Height PL4	500
Packaging Length PL1	210
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	108
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet

Packaging Volume PL1	0,002205
Packaging Volume PL4	0,48
Packaging Weight PL1	2,8
Packaging Weight PL4	305,8
Packaging Width PL1	175
Packaging Width PL4	800

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+