


Uponor Ecoflex Thermo Single 25x2,3/140

1018109

- Heating and Cooling
- One medium pipe PE-Xa with oxygen barrier, SDR 11
- Max. load 6 bar / 95°C
- PEX foam, HDPE casing



Application information Uponor Ecoflex Thermo Single

Specification

- Flexible, pre-insulated, self-compensating plastic pipe system produced based on EN 15632 and EN 17414.
- Medium pipe: Cross-linked polyethylene (PE-Xa) pipe based on EN ISO 15875, natural coloured, PN 6 (SDR 11), oxygen tightness based on EN 15632.
- Insulating material: Closed-cell PE-X foam, permanently elastic, ageing-resistant
- Casing pipe: Corrugated polyethylene (HDPE)

Application


- Transport of heating and cooling water for buried installations.
- Heating operating temperature 80°C based on EN 15632
- Malfunction temperature 95°C
- Static verification for heavy traffic load of 60 tons

Certification

- Approvals should be checked by local responsible person

Uponor Ecoflex Thermo Single 25x2,3/140

1018109



Measurements

Bending radius M	0,25
Outer Diameter_do	140
Outer Diameter_do1	25
Wall thickness_s1	2,3

Product code

Item no EAN	6414905200252
Item no GF	35001018109
Item no GTIN	06414905200252
Item no LVI	3010212
Item no VVS	087807025

Dimensions

Item Unit Height	140
Item Unit Length	1000
Item Unit Weight	1,18
Item Unit Width	140
Item_UOM	m

Packaging

Packaging GTIN PL1	06414905437115
Packaging Height PL1	2200
Packaging Length PL1	1500
Packaging Quantity PL1	200
Packaging Type PL1	Coil
Packaging Volume PL1	7,26
Packaging Weight PL1	236
Packaging Width PL1	2200

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com