


Uponor Ecoflex Thermo Pipe Twin 2x50x4,6/200

1018137

- Heating and Cooling
- Two medium pipes PE-Xa with oxygen barrier, SDR 11
- Max. load 6 bar / 95°C
- Coloured centre profil to avoid confusion of flow and return line
- PEX foam, HDPE casing



Application information Uponor Ecoflex Thermo Pipe Twin

Specification

- Flexible, pre-insulated, self-compensating plastic pipe system produced based on EN 15632 and EN 17414.
- Medium pipe: Cross-linked polyethylene (PE-Xa) pipe based on EN ISO 15875, natural coloured, PN 6 (SDR 11), oxygen tightness based on EN 15632.
- Insulating material: Closed-cell PE-X foam, permanently elastic, ageing-resistant
- Casing pipe: Corrugated polyethylene (HDPE)

Application

- Transport of heating and cooling water for buried installations.
- Heating operating temperature 80°C based on EN 15632
- Malfunction temperature 95°C
- Static verification for heavy traffic load of 60 tons

Certification

- Approvals should be checked by local responsible person

Uponor Ecoflex Thermo Pipe Twin 2x50x4,6/200

1018137



Measurements

Bending radius M	1
Outer Diameter_do	200
Outer Diameter_do1	50
Outer Diameter_do2	50
Wall thickness_s1	4,6
Wall thickness_s2	4,6

Product code

Item no EAN	6414905210510
Item no GF	35001018137
Item no GTIN	06414905210510
Item no LVI	3010225
Item no NOBB	41945256
Item no NRF	8360505
Item no RSK	2190413
Item no VVS	087809050

Dimensions

Item Unit Height	175
Item Unit Length	1000
Item Unit Weight	3,59
Item Unit Width	175
Item_UOM	m

Packaging

Packaging GTIN PL1	06414905437399
Packaging Height PL1	2400
Packaging Length PL1	1400
Packaging Quantity PL1	100
Packaging Type PL1	Coil

Packaging Volume PL1	8,064
Packaging Weight PL1	359
Packaging Width PL1	2400

Documents

Page with all documents 

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com