

Uponor Ecoflex Quattro Pipe 2x25x2,3-2x25x3,5/175

1018147

- Heating and warm tap water with circulation
- Four medium pipe PE-Xa, SDR 11 and 7,4
- Max. load 6 bar heating / 10 bar tap water / 95°C
- PEX foam, HDPE casing
- Coloured centre profil to avoid confusion between the lines



Application information Uponor Ecoflex Quattro Pipe

Specification

- Flexible, pre-insulated, self-compensating plastic pipe system
- Medium pipe: Cross-linked polyethylene (PE-Xa) pipe based on EN ISO 15875, natural coloured, PN 6 (SDR 11) and PN10 (SDR 7,4), Oxygen tightness based on EN 15632 for heating pipes
- Insulating material: closed-cell PE-X foam, permanently elastic, ageing-resistant
- Casing pipe: Corrugated polyethylene (HDPE)

Application

- Transport of heating and warm tap water for buried installations.
- Heating operating temperature 80°C based on EN 15632
- Tap water operating temperature 70°C based on EN ISO 15875
- Malfunction temperature 95°C
- Static verification for heavy traffic load of 60 tons

Certification

- Approvals should be checked by local responsible person

Uponor Ecoflex Quattro Pipe 2x25x2,3-2x25x3,5/175

1018147



Measurements

Bending radius M	0,8
Outer Diameter_do	175
Outer Diameter_do1	25
Outer Diameter_do2	25
Outer Diameter_do3	25
Wall thickness_s1	2,3
Wall thickness_s2	3,5
Wall thickness_s3	3,5

Product code

Item no EAN	4021598111776
Item no GF	35001018147
Item no GTIN	04021598111776
Item no VVS	087817850

Dimensions

Item Unit Height	175
Item Unit Length	1000
Item Unit Weight	2,41
Item Unit Width	175
Item_UOM	m

Packaging

Packaging GTIN PL1	06414905473359
Packaging Height PL1	2400
Packaging Length PL1	1800
Packaging Quantity PL1	200
Packaging Type PL1	Coil
Packaging Volume PL1	10,368
Packaging Weight PL1	482

Packaging Width PL1

2400

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com