


Uponor Wipex fix point bushing G1

1018302

- Cylindric thread G" with sealing ring
- 6 bar, SDR 11 / 10bar, SDR 7,4
- DR = dezincification resistance brass



Application information Uponor Wipex fix point bushing

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application


- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex fix point bushing G1

1018302



Measurements

Cylindric_thread_G	1
Cylindric_thread_G1	1
LENGTH_L	54
z1	42

Product code

Item no EAN	7331541099721
Item no GF	35001018302
Item no GTIN	07331541099721
Item no LVI	1938025
Item no NOBB	41946183
Item no NRF	8360761
Item no RSK	2410652
Item no VVS	087837025

Dimensions

Item Unit Height	50
Item Unit Length	45
Item Unit Weight	0,22
Item Unit Width	45
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905437788
Packaging GTIN PL3	06414905446605
Packaging Height PL1	50
Packaging Height PL3	104
Packaging Length PL1	45
Packaging Length PL3	250
Packaging Quantity PL1	1

Packaging Quantity PL3	30
Packaging Type PL1	Plastic_Bag
Packaging Type PL3	Box
Packaging Volume PL1	0,00010125
Packaging Volume PL3	0,00351
Packaging Weight PL1	0,23
Packaging Weight PL3	7
Packaging Width PL1	45
Packaging Width PL3	135

Documents

Page with all documents 

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com