

Uponor Wipex tee G3-G3-G3

1018348

- Cylindric thread G" with sealing ring
- 6 bar, SDR 11 / 10 bar, SDR 7,4
- DR = dezincification resistance brass



Application information Uponor Wipex tee

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex tee G3-G3-G3

1018348



Measurements

Cylindric_thread_G	3
Length (l1)	75
Length (l2)	75
Length (l3)	75

Product code

Item no EAN	7331541098908
Item no GF	35001018348
Item no GTIN	07331541098908
Item no LVI	1933080
Item no NOBB	48326104
Item no NRF	8360703
Item no RSK	2410625
Item no VVS	087842014

Dimensions

Item Unit Height	111
Item Unit Length	152
Item Unit Weight	2,499
Item Unit Width	220
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905260157
Packaging GTIN PL3	06414905260164
Packaging Height PL1	114
Packaging Height PL3	155
Packaging Length PL1	155
Packaging Length PL3	272
Packaging Quantity PL1	1

Packaging Quantity PL3	3
Packaging Type PL1	Plastic_Bag
Packaging Type PL3	Box
Packaging Volume PL1	0,00394041
Packaging Volume PL3	0,01054
Packaging Weight PL1	2,517
Packaging Weight PL3	7,731
Packaging Width PL1	223
Packaging Width PL3	250

Documents

Page with all documents 

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com