

Uponor Wipex elbow G2-G2

1018352

- Cylindric thread G" with sealing ring
- 6 bar, SDR 11 / 10 bar, SDR 7,4
- DR = dezincification resistance brass



Application information Uponor Wipex elbow

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex elbow G2-G2

1018352

**Measurements**

Cylindric_thread_G	2
Length (l1)	55
Length (l2)	55

Product code

Item no EAN	7331541098847
Item no GF	35001018352
Item no GTIN	07331541098847
Item no LVI	1935050
Item no NOBB	41945884
Item no NRF	8360692
Item no RSK	2410620
Item no VVS	087832012

Dimensions

Item Unit Height	71
Item Unit Length	98
Item Unit Weight	0,854
Item Unit Width	98
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905260232
Packaging GTIN PL3	06414905260249
Packaging GTIN PL4	06414905260256
Packaging Height PL1	73
Packaging Height PL3	140
Packaging Height PL4	700
Packaging Length PL1	100
Packaging Length PL3	248

Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL3	5
Packaging Quantity PL4	480
Packaging Type PL1	Plastic_Bag
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00073
Packaging Volume PL3	0,00479136
Packaging Volume PL4	0,672
Packaging Weight PL1	0,891
Packaging Weight PL3	4,365
Packaging Weight PL4	464,43
Packaging Width PL1	100
Packaging Width PL3	138
Packaging Width PL4	800

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com