

Uponor Wipex elbow G3-G3

1018353

- Cylindric thread G" with sealing ring
- 6 bar, SDR 11 / 10 bar, SDR 7,4
- DR = dezincification resistance brass



Application information Uponor Wipex elbow

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex elbow G3-G3

1018353

**Measurements**

Cylindric_thread_G	3
Length (l1)	75
Length (l2)	75

Product code

Item no EAN	7331541098854
Item no GF	35001018353
Item no GTIN	07331541098854
Item no LVI	1935080
Item no NOBB	41945892
Item no NRF	8360693
Item no RSK	2410621
Item no VVS	087832014

Dimensions

Item Unit Height	102
Item Unit Length	120
Item Unit Weight	2,184
Item Unit Width	120
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905260263
Packaging GTIN PL3	06414905260270
Packaging Height PL1	140
Packaging Height PL3	140
Packaging Length PL1	248
Packaging Length PL3	248
Packaging Quantity PL1	1
Packaging Quantity PL3	2

Packaging Type PL1	Plastic_Bag
Packaging Type PL3	Box
Packaging Volume PL1	0,00479136
Packaging Volume PL3	0,00479136
Packaging Weight PL1	4,463
Packaging Weight PL3	4,558
Packaging Width PL1	138
Packaging Width PL3	138

Documents

Page with all documents 

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com