


Uponor Wipex sleeve G1-G1

1018355

- Cylindric thread G" with sealing ring
- 6 bar, SDR 11 / 10 bar, SDR 7,4
- DR = dezincification resistance brass



Application information Uponor Wipex sleeve

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application


- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex sleeve G1-G1

1018355



Measurements

Cylindric_thread_G	1
LENGTH_L	30

Product code

Item no EAN	7331541098816
Item no GF	35001018355
Item no GTIN	07331541098816
Item no LVI	1936025
Item no NOBB	48326142
Item no NRF	8362412
Item no RSK	2410614
Item no VVS	087830008

Dimensions

Item Unit Height	28
Item Unit Length	48
Item Unit Weight	0,182
Item Unit Width	48
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905260287
Packaging GTIN PL3	06414905260294
Packaging GTIN PL4	06414905260300
Packaging Height PL1	30
Packaging Height PL3	145
Packaging Height PL4	800
Packaging Length PL1	50
Packaging Length PL3	268
Packaging Length PL4	1200

Packaging Quantity PL1	1
Packaging Quantity PL3	40
Packaging Quantity PL4	4000
Packaging Type PL1	Plastic_Bag
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,000075
Packaging Volume PL3	0,009715
Packaging Volume PL4	0,768
Packaging Weight PL1	0,186
Packaging Weight PL3	7,46
Packaging Weight PL4	777,5
Packaging Width PL1	50
Packaging Width PL3	250
Packaging Width PL4	800

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com