

Uponor Wipex sleeve G1 1/4-G1 1/4

1018356

- Cylindric thread G" with sealing ring
- 6 bar, SDR 11 / 10 bar, SDR 7,4
- DR = dezincification resistance brass



Application information Uponor Wipex sleeve

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex sleeve G1 1/4-G1 1/4

1018356



Measurements

Cylindric_thread_G	1 1/4
LENGTH_L	37

Product code

Item no EAN	7331541098786
Item no GF	35001018356
Item no GTIN	07331541098786
Item no LVI	1936032
Item no NOBB	41945846
Item no NRF	8360681
Item no RSK	2410615
Item no VVS	087830010

Dimensions

Item Unit Height	32
Item Unit Length	53
Item Unit Weight	0,212
Item Unit Width	32
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905437863
Packaging GTIN PL3	06414905446681
Packaging GTIN PL4	06414905490691
Packaging Height PL1	35
Packaging Height PL3	145
Packaging Height PL4	750
Packaging Length PL1	55
Packaging Length PL3	250
Packaging Length PL4	1200

Packaging Quantity PL1	1
Packaging Quantity PL3	25
Packaging Quantity PL4	2400
Packaging Type PL1	Plastic_Bag
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,000067375
Packaging Volume PL3	0,0050025
Packaging Volume PL4	0,72
Packaging Weight PL1	0,217
Packaging Weight PL3	5,541
Packaging Weight PL4	556,936
Packaging Width PL1	35
Packaging Width PL3	138
Packaging Width PL4	800

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com