

Uponor Wipex sleeve G2-G2

1018357

- Cylindric thread G" with sealing ring
- 6 bar, SDR 11 / 10 bar, SDR 7,4
- DR = dezincification resistance brass



Application information Uponor Wipex sleeve

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex sleeve G2-G2

1018357



Measurements

Cylindric_thread_G	2
LENGTH_L	45

Product code

Item no EAN	7331541098793
Item no GF	35001018357
Item no GTIN	07331541098793
Item no LVI	1936050
Item no NOBB	41945854
Item no NRF	8360682
Item no RSK	2410616
Item no VVS	087830012

Dimensions

Item Unit Height	45
Item Unit Length	74
Item Unit Weight	0,413
Item Unit Width	74
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905437870
Packaging GTIN PL3	06414905446698
Packaging Height PL1	48
Packaging Height PL3	145
Packaging Length PL1	77
Packaging Length PL3	250
Packaging Quantity PL1	1
Packaging Quantity PL3	15
Packaging Type PL1	Plastic_Bag

Packaging Type PL3	Box
Packaging Volume PL1	0,000284592
Packaging Volume PL3	0,0050025
Packaging Weight PL1	0,418
Packaging Weight PL3	6,42
Packaging Width PL1	77
Packaging Width PL3	138

Documents

Page with all documents 

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com