


Uponor Wipex flange F25/4-85/G1

1018359

- Cylindric thread G" with sealing ring
- 6 bar, SDR 11 / 10 bar, SDR 7,4
- DR = dezincification resistance brass



Application information Uponor Wipex flange

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application


- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex flange F25/4-85/G1

1018359



Measurements

Cylindric_thread_G	1
Outer Diameter_do	115
Z Measurement k	85

Product code

Item no EAN	7331541099295
Item no GF	35001018359
Item no GTIN	07331541099295
Item no LVI	1938125
Item no NOBB	41946115
Item no NRF	8360751
Item no RSK	2410645
Item no VVS	087844025

Dimensions

Item Unit Height	25
Item Unit Length	111
Item Unit Weight	1,245
Item Unit Width	111
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905437894
Packaging GTIN PL3	06414905446711
Packaging Height PL1	28
Packaging Height PL3	155
Packaging Length PL1	114
Packaging Length PL3	272
Packaging Quantity PL1	1
Packaging Quantity PL3	10

Packaging Type PL1	Plastic_Bag
Packaging Type PL3	Box
Packaging Volume PL1	0,000363888
Packaging Volume PL3	0,01054
Packaging Weight PL1	1,251
Packaging Weight PL3	12,636
Packaging Width PL1	114
Packaging Width PL3	250

Documents

Page with all documents 

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com