

Uponor Wipex flange F40/4-110/G1 1/2

1018361

- Cylindric thread G" with sealing ring
- 6 bar, SDR 11 / 10 bar, SDR 7,4
- DR = dezincification resistance brass



Application information Uponor Wipex flange

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex flange F40/4-110/G1 1/2

1018361

**Measurements**

Cylindric_thread_G	1 1/2
Outer Diameter_do	150
Z Measurement k	110

Product code

Item no EAN	7331541099318
Item no GF	35001018361
Item no GTIN	07331541099318
Item no NOBB	41946134
Item no NRF	8360753
Item no RSK	2410647
Item no VVS	087844040

Dimensions

Item Unit Height	29
Item Unit Length	150
Item Unit Weight	2,574
Item Unit Width	150
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905437917
Packaging GTIN PL3	06414905446735
Packaging Height PL1	31
Packaging Height PL3	115
Packaging Length PL1	152
Packaging Length PL3	355
Packaging Quantity PL1	1
Packaging Quantity PL3	5
Packaging Type PL1	Plastic_Bag

Packaging Type PL3	Box
Packaging Volume PL1	0,000716224
Packaging Volume PL3	0,010410375
Packaging Weight PL1	2,586
Packaging Weight PL3	12,95
Packaging Width PL1	152
Packaging Width PL3	255

Documents

Page with all documents 

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com