

Uponor Wipex flange F50/4-125/G2

1018362

- Cylindric thread G" with sealing ring
- 6 bar, SDR 11 / 10 bar, SDR 7,4
- DR = dezincification resistance brass



Application information Uponor Wipex flange

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex flange F50/4-125/G2

1018362

**Measurements**

Cylindric_thread_G	2
Outer Diameter_do	165
Z Measurement k	125

Product code

Item no EAN	7331541099325
Item no GF	35001018362
Item no GTIN	07331541099325
Item no LVI	1938150
Item no NOBB	41946145
Item no NRF	8360754
Item no RSK	2410648
Item no VVS	087844050

Dimensions

Item Unit Height	22
Item Unit Length	165
Item Unit Weight	3,028
Item Unit Width	165
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905437924
Packaging GTIN PL3	06414905446742
Packaging GTIN PL4	06414905490721
Packaging Height PL1	25
Packaging Height PL3	145
Packaging Height PL4	700
Packaging Length PL1	168
Packaging Length PL3	272

Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL3	4
Packaging Quantity PL4	192
Packaging Type PL1	Plastic_Bag
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,0007056
Packaging Volume PL3	0,0100572
Packaging Volume PL4	0,672
Packaging Weight PL1	3,043
Packaging Weight PL3	12,337
Packaging Weight PL4	617,19
Packaging Width PL1	168
Packaging Width PL3	255
Packaging Width PL4	800

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com