

Uponor Wipex flange F65/8-145/2 1/2

1018363

- Cylindric thread G" with sealing ring
- 6 bar, SDR 11 / 10 bar, SDR 7,4
- DR = dezincification resistance brass



Application information Uponor Wipex flange

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex flange F65/8-145/2 1/2

1018363



Measurements

Cylindric_thread_G	2 1/2
Outer Diameter_do	185
Z Measurement k	145

Product code

Item no EAN	7331541099332
Item no GF	35001018363
Item no GTIN	07331541099332
Item no NOBB	41946153
Item no NRF	8360755
Item no RSK	2410649
Item no VVS	087844065

Dimensions

Item Unit Height	26
Item Unit Length	185
Item Unit Weight	3,713
Item Unit Width	185
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905437931
Packaging GTIN PL3	06414905446759
Packaging Height PL1	28
Packaging Height PL3	145
Packaging Length PL1	187
Packaging Length PL3	272
Packaging Quantity PL1	1
Packaging Quantity PL3	3
Packaging Type PL1	Plastic_Bag

Packaging Type PL3	Box
Packaging Volume PL1	0,000979132
Packaging Volume PL3	0,0100572
Packaging Weight PL1	3,728
Packaging Weight PL3	11,388
Packaging Width PL1	187
Packaging Width PL3	255

Documents

Page with all documents 

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com