

## Uponor Wipex flange F65/8-145/2 1/2

**1018363**

- Cylindric thread G" with sealing ring
- 6 bar, SDR 11 / 10 bar, SDR 7,4
- DR = dezincification resistance brass



### Application information Uponor Wipex flange

#### Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

#### Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

#### Certification

- Approvals should be checked by local responsible person

## Uponor Wipex flange F65/8-145/2 1/2

1018363

**Measurements**

Cylindric_thread_G	2 1/2
Outer Diameter_do	185
Z Measurement k	145

**Product code**

Item no EAN	7331541099332
Item no GF	35001018363
Item no GTIN	07331541099332
Item no NOBB	41946153
Item no NRF	8360755
Item no RSK	2410649
Item no VVS	087844065

**Dimensions**

Item Unit Height	26
Item Unit Length	185
Item Unit Weight	3,713
Item Unit Width	185
Item_UOM	pce

**Packaging**

Packaging GTIN PL1	06414905437931
Packaging GTIN PL3	06414905446759
Packaging Height PL1	28
Packaging Height PL3	145
Packaging Length PL1	187
Packaging Length PL3	272
Packaging Quantity PL1	1
Packaging Quantity PL3	3
Packaging Type PL1	Plastic_Bag

Packaging Type PL3	Box
Packaging Volume PL1	0,000979132
Packaging Volume PL3	0,0100572
Packaging Weight PL1	3,728
Packaging Weight PL3	11,388
Packaging Width PL1	187
Packaging Width PL3	255

## Documents

Page with all documents 

### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211

[www.uponor.com](http://www.uponor.com)