

## Uponor Wipex flange F80/8-160/G3

**1018364**

- Cylindric thread G" with sealing ring
- 6 bar, SDR 11 / 10 bar, SDR 7,4
- DR = dezincification resistance brass



### Application information Uponor Wipex flange

#### Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

#### Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

#### Certification

- Approvals should be checked by local responsible person

## Uponor Wipex flange F80/8-160/G3

1018364

**Measurements**

Cylindric_thread_G	3
Outer Diameter_do	200
Z Measurement k	160

**Product code**

Item no EAN	7331541099349
Item no GF	35001018364
Item no GTIN	07331541099349
Item no LVI	1938180
Item no NOBB	41946164
Item no NRF	8360756
Item no RSK	2410650
Item no VVS	087844080

**Dimensions**

Item Unit Height	28
Item Unit Length	200
Item Unit Weight	4,183
Item Unit Width	200
Item_UOM	pce

**Packaging**

Packaging GTIN PL1	06414905437948
Packaging GTIN PL3	06414905446766
Packaging Height PL1	30
Packaging Height PL3	155
Packaging Length PL1	202
Packaging Length PL3	255
Packaging Quantity PL1	1
Packaging Quantity PL3	3

Packaging Type PL1	Plastic_Bag
Packaging Type PL3	Box
Packaging Volume PL1	0,00122412
Packaging Volume PL3	0,01067175
Packaging Weight PL1	4,198
Packaging Weight PL3	12,746
Packaging Width PL1	202
Packaging Width PL3	270

## Documents

Page with all documents 

### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211  
E  
communications@georgfischer.  
com