

## Uponor Wipex flange F100/8-180/G4

**1018365**

- Cylindric thread G" with sealing ring
- 6 bar, SDR 11 / 10 bar, SDR 7,4
- DR = dezincification resistance brass



### Application information Uponor Wipex flange

#### Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

#### Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

#### Certification

- Approvals should be checked by local responsible person

## Uponor Wipex flange F100/8-180/G4

1018365



### Measurements

Cylindric_thread_G	4
Outer Diameter_do	220
Z Measurement k	180

### Product code

Item no EAN	7331541099356
Item no GF	35001018365
Item no GTIN	07331541099356
Item no NOBB	41946172
Item no NRF	8360757
Item no RSK	2410651
Item no VVS	087844091

### Dimensions

Item Unit Height	32
Item Unit Length	223
Item Unit Weight	4,441
Item Unit Width	223
Item_UOM	pce

### Packaging

Packaging GTIN PL1	06414905437955
Packaging GTIN PL3	06414905446773
Packaging Height PL1	34
Packaging Height PL3	155
Packaging Length PL1	225
Packaging Length PL3	272
Packaging Quantity PL1	1
Packaging Quantity PL3	3
Packaging Type PL1	Plastic_Bag

Packaging Type PL3	Box
Packaging Volume PL1	0,00172125
Packaging Volume PL3	0,01054
Packaging Weight PL1	4,451
Packaging Weight PL3	13,682
Packaging Width PL1	225
Packaging Width PL3	250

## Documents

Page with all documents



### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211

[www.uponor.com](http://www.uponor.com)