


Uponor Wipex reducer male x female G1 1/4-G1

1018368

- Material: brass
- Female & male thread



Application information Uponor Wipex reducer male x female

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application


- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex reducer male x female G1 1/4-G1

1018368



Measurements

Cylindric_thread_G	1 1/4
Cylindric_thread_G1	1
LENGTH_L	36
z1	20

Product code

Item no EAN	7331541099028
Item no GF	35001018368
Item no GTIN	07331541099028
Item no LVI	1934025
Item no NOBB	41946024
Item no NRF	8360731
Item no RSK	2410636
Item no VVS	087836151

Dimensions

Item Unit Height	39
Item Unit Length	50
Item Unit Weight	0,236
Item Unit Width	50
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905437962
Packaging GTIN PL3	06414905446780
Packaging GTIN PL4	06414905490738
Packaging Height PL1	41
Packaging Height PL3	145
Packaging Height PL4	750
Packaging Length PL1	52

Packaging Length PL3	250
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL3	25
Packaging Quantity PL4	2400
Packaging Type PL1	Plastic_Bag
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,000110864
Packaging Volume PL3	0,0050025
Packaging Volume PL4	0,72
Packaging Weight PL1	0,241
Packaging Weight PL3	6,134
Packaging Weight PL4	613,864
Packaging Width PL1	52
Packaging Width PL3	138
Packaging Width PL4	800

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com