


Uponor Wipex reducer male x female G1 1/4-G1

1018368



Application information Uponor Wipex reducer male x female

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application


- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex reducer male x female G1 1/4-G1

1018368



Technical data

Item (unit of measurement) pce

Item no VVS 087836151

Item no LVI 1934025

Item no NRF 8360731

Length (l) 36 mm

Packaging Quantity PL1 1

Packaging Quantity PL3 25

Packaging Quantity PL4 2400

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
FinlandT +358 (0)20 129 211
E info@uponor.com
F +358 (0)20 129 2841

www.uponor.com