


## Uponor Wipex reducer male x female G1 1/2-G1 1/4

1018369



### Application information Uponor Wipex reducer male x female

#### Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

#### Application


- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

#### Certification

- Approvals should be checked by local responsible person

## Uponor Wipex reducer male x female G1 1/2-G1 1/4

1018369



### Technical data

Item (unit of measurement) pce

Item no VVS 089770603

Item no NRF 8360732

Length (l) 39 mm

Packaging Quantity PL1 1

Packaging Quantity PL3 25

Packaging Quantity PL4 2400

### Documents

Page with all documents



#### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211  
E info@uponor.com  
F +358 (0)20 129 2841

www.uponor.com