

Uponor Wipex reducer male x female G2-G1

1018371

- Material: brass
- Female & male thread



Application information Uponor Wipex reducer male x female

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex reducer male x female G2-G1

1018371

**Measurements**

Cylindric_thread_G	2
Cylindric_thread_G1	1
LENGTH_L	41
z1	21

Product code

Item no EAN	7331541099042
Item no GF	35001018371
Item no GTIN	07331541099042
Item no LVI	1934040
Item no NOBB	41946043
Item no NRF	8360733
Item no RSK	2410638
Item no VVS	087836165

Dimensions

Item Unit Height	80
Item Unit Length	42
Item Unit Weight	0,406
Item Unit Width	38
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905437986
Packaging GTIN PL3	06414905446803
Packaging Height PL1	83
Packaging Height PL3	145
Packaging Length PL1	45
Packaging Length PL3	250
Packaging Quantity PL1	1

Packaging Quantity PL3	15
Packaging Type PL1	Plastic_Bag
Packaging Type PL3	Box
Packaging Volume PL1	0,0002988
Packaging Volume PL3	0,0050025
Packaging Weight PL1	0,41
Packaging Weight PL3	6,326
Packaging Width PL1	80
Packaging Width PL3	138

Documents

[Page with all documents](#)

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com