

Uponor Wipex reducer male x female G2 1/2-G2

1018373

- Material: brass
- Female & male thread



Application information Uponor Wipex reducer male x female

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex reducer male x female G2 1/2-G2

1018373

**Measurements**

Cylindric_thread_G	2 1/2
Cylindric_thread_G1	2
LENGTH_L	48
z1	26

Product code

Item no EAN	7331541098977
Item no GF	35001018373
Item no GTIN	07331541098977
Item no NOBB	41946062
Item no NRF	8360735
Item no RSK	2410640
Item no VVS	087836174

Dimensions

Item Unit Height	85
Item Unit Length	54
Item Unit Weight	0,705
Item Unit Width	85
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905438006
Packaging GTIN PL3	06414905446827
Packaging GTIN PL4	06414905490752
Packaging Height PL1	87
Packaging Height PL3	145
Packaging Height PL4	700
Packaging Length PL1	56
Packaging Length PL3	250

Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL3	6
Packaging Quantity PL4	576
Packaging Type PL1	Plastic_Bag
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,000423864
Packaging Volume PL3	0,0050025
Packaging Volume PL4	0,672
Packaging Weight PL1	0,709
Packaging Weight PL3	4,418
Packaging Weight PL4	449,128
Packaging Width PL1	87
Packaging Width PL3	138
Packaging Width PL4	800

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com