

Uponor Wipex reducer male x female G3-G1

1018374

- Material: brass
- Female & male thread



Application information Uponor Wipex reducer male x female

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex reducer male x female G3-G1

1018374



Measurements

Cylindric_thread_G	3
Cylindric_thread_G1	1
LENGTH_L	47
z1	23

Product code

Item no EAN	7331541099035
Item no GF	35001018374
Item no GTIN	07331541099035
Item no LVI	1934060
Item no NOBB	41946077
Item no NRF	8360736
Item no RSK	2410641
Item no VVS	087836177

Dimensions

Item Unit Height	50
Item Unit Length	105
Item Unit Weight	0,945
Item Unit Width	105
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905438013
Packaging GTIN PL3	06414905446834
Packaging GTIN PL4	06414905490769
Packaging Height PL1	53
Packaging Height PL3	145
Packaging Height PL4	750
Packaging Length PL1	108

Packaging Length PL3	250
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL3	6
Packaging Quantity PL4	576
Packaging Type PL1	Plastic_Bag
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,000618192
Packaging Volume PL3	0,0050025
Packaging Volume PL4	0,72
Packaging Weight PL1	0,949
Packaging Weight PL3	5,751
Packaging Weight PL4	577,096
Packaging Width PL1	108
Packaging Width PL3	138
Packaging Width PL4	800

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com