

## Uponor Wipex reducer male x female G3-G1 1/4

**1018375**

- Material: brass
- Female & male thread



### Application information Uponor Wipex reducer male x female

#### Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

#### Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

#### Certification

- Approvals should be checked by local responsible person

## Uponor Wipex reducer male x female G3-G1 1/4

1018375

**Measurements**

Cylindric_thread_G	3
Cylindric_thread_G1	1 1/4
LENGTH_L	51
z1	27

**Product code**

Item no EAN	7331541098991
Item no GF	35001018375
Item no GTIN	07331541098991
Item no LVI	1934070
Item no NOBB	41946081
Item no NRF	8360737
Item no RSK	2410642
Item no VVS	087836178

**Dimensions**

Item Unit Height	55
Item Unit Length	105
Item Unit Weight	1,04
Item Unit Width	105
Item_UOM	pce

**Packaging**

Packaging GTIN PL1	06414905438020
Packaging GTIN PL3	06414905446841
Packaging Height PL1	58
Packaging Height PL3	145
Packaging Length PL1	108
Packaging Length PL3	272
Packaging Quantity PL1	1

Packaging Quantity PL3	10
Packaging Type PL1	Plastic_Bag
Packaging Type PL3	Box
Packaging Volume PL1	0,000676512
Packaging Volume PL3	0,00986
Packaging Weight PL1	1,047
Packaging Weight PL3	10,597
Packaging Width PL1	108
Packaging Width PL3	250

## Documents

Page with all documents 

### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211  
E  
communications@georgfischer.  
com