

Uponor Wipex reducer male x female G3-G2

1018376

- Material: brass
- Female & male thread



Application information Uponor Wipex reducer male x female

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex reducer male x female G3-G2

1018376



Measurements

Cylindric_thread_G	3
Cylindric_thread_G1	2
LENGTH_L	55
z1	31

Product code

Item no EAN	7331541099004
Item no GF	35001018376
Item no GTIN	07331541099004
Item no LVI	1934080
Item no NOBB	41946096
Item no NRF	8360738
Item no RSK	2410643
Item no VVS	087836180

Dimensions

Item Unit Height	110
Item Unit Length	55
Item Unit Weight	1,018
Item Unit Width	110
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905438037
Packaging GTIN PL3	06414905446858
Packaging Height PL1	113
Packaging Height PL3	270
Packaging Length PL1	58
Packaging Length PL3	255
Packaging Quantity PL1	1

Packaging Quantity PL3	10
Packaging Type PL1	Plastic_Bag
Packaging Type PL3	Box
Packaging Volume PL1	0,000740602
Packaging Volume PL3	0,0103275
Packaging Weight PL1	1,021
Packaging Weight PL3	10,303
Packaging Width PL1	113
Packaging Width PL3	150

Documents

[Page with all documents](#)

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com